

Outside Screw and Yoke Gate Valves

Outside screw and yoke gate valves are recommended for service indoors and in pits outdoors. They are not recommended for throttling service. The stem indicates at a glance whether or not the valve is open. Smaller sizes, 3/4 through 2 in. NPS inclusive, are of bronze. Large sizes, 2 1/2 through 14 in. NPS inclusive, are of iron, bronze mounted. One manufacturer makes valves of bronze up through the 3 in. size. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

Fig. 3299-200-FLF, Fig. 3299-200-GLF, Fig. 3299-200-FxGLF

Fig. 3299 Resilient Seated Gate Valve. Rated Working Pressure 200 psi (1380 kPa). Available with the end connections listed below:

<i>Model No.</i>	<i>Size in. (mm)</i>	<i>End Connections</i>
Fig. 3299-200-FLF	2 1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Flange (ANSI, ISO, JIS)
Fig. 3299-200-GLF	2 1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Grooved × Grooved
Fig. 3299-200-FxGLF	2 1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Groove (ANSI, ISO, JIS)

Company Name:	Lichfield Fire & Safety Equipment Co Ltd
Company Address:	Unit 8 Calibre Industrial Park, Laches Close, Four Ashes, Wolverhampton, Staffordshire WV10 7DZ
Company Website:	http://www.lifeco-uk.com
New/Updated Product Listing:	No
Listing Country:	United Kingdom
Certification Type:	FM Approved

Outside Screw and Yoke Gate Valves

Outside screw and yoke gate valves are recommended for service indoors and in pits outdoors. They are not recommended for throttling service. The stem indicates at a glance whether or not the valve is open. Smaller sizes, 3/4 through 2 in. NPS inclusive, are of bronze. Large sizes, 2 1/2 through 14 in. NPS inclusive, are of iron, bronze mounted. One manufacturer makes valves of bronze up through the 3 in. size. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

Fig. 3299-250-FLF, Fig. 3299-250-GLF, Fig. 3299-250-FxGLF

Fig. 3299 Resilient Seated Gate Valve. Rated Working Pressure 250 psi (1725 kPa). Available with the end connections listed below:

<i>Model No.</i>	<i>Size in. (mm)</i>	<i>End Connections</i>
Fig. 3299-250-FLF	2 1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Flange (ANSI, ISO, JIS)
Fig. 3299-250-GLF	2 1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Grooved × Grooved
Fig. 3299-250-FxGLF	2 1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Groove (ANSI, ISO, JIS)

Company Name:	Lichfield Fire & Safety Equipment Co Ltd
Company Address:	Unit 8 Calibre Industrial Park, Laches Close, Four Ashes, Wolverhampton, Staffordshire WV10 7DZ
Company Website:	http://www.lifeco-uk.com
New/Updated Product Listing:	No
Listing Country:	United Kingdom
Certification Type:	FM Approved

Outside Screw and Yoke Gate Valves

Outside screw and yoke gate valves are recommended for service indoors and in pits outdoors. They are not recommended for throttling service. The stem indicates at a glance whether or not the valve is open. Smaller sizes, 3/4 through 2 in. NPS inclusive, are of bronze. Large sizes, 2 1/2 through 14 in. NPS inclusive, are of iron, bronze mounted. One manufacturer makes valves of bronze up through the 3 in. size. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

Fig. 3299-300-FLF, Fig. 3299-300-GLF, Fig. 3299-300-FxGLF

Fig. 3299 Resilient Seated Gate Valve. Rated Working Pressure 300 psi (2068 kPa). Available with the end connections listed below:

<i>Model No.</i>	<i>Size in. (mm)</i>	<i>End Connections</i>
Fig. 3299-300-FLF	2 1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Flange (ANSI, ISO, JIS)
Fig. 3299-300-GLF	2 1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Grooved × Grooved
Fig. 3299-300-FxGLF	2 1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	Flange × Groove (ANSI, ISO, JIS)

Company Name:	Lichfield Fire & Safety Equipment Co Ltd
Company Address:	Unit 8 Calibre Industrial Park, Laches Close, Four Ashes, Wolverhampton, Staffordshire WV10 7DZ
Company Website:	http://www.lifeco-uk.com
New/Updated Product Listing:	No
Listing Country:	United Kingdom
Certification Type:	FM Approved